

21.5" Embedded Touch PC

FT215V40CAPOB



- Allwinner® V40 Cortex™ A7 QuadCore Processor
 - 1GB RAM Memory & 8GB FLASH Storage
 - Pre-installed Android 6.0 operating system
 - Anti-glare surface treatment (chemical etching)
 - 10-Finger-Multi Touch Capacitive Touch Panel
 - 1.1mm cover glass with 7H surface hardness
 - Optically bonded Touch Panel to LCD Panel
 - Patented IP65 front with silicon seal
 - Integrated W-LAN module
 - 2 year guarantee
- *Optional: integrated GPS, Bluetooth, 3G/4G, POE module*




faytech's Embedded Touch PCs have a pre-installed Android 6.0 operating system and are equipped with W-LAN module. The device has IP65 water- and dust proof front panels and capacitive 10-finger multitouch. All the PCs have VESA 75 or VESA 100 screw patterns on the back, while the 13.3" to 21.5" come with their own desktop stand included.

The Embedded PC is powered by the powerful embedded V40 QuadCore mainboard, with 1G DDR3 RAM, 8GB flash memory, a SATA connector and SD card slot for further storage expansion.

This device has an optically bonded touch panel, which will improve the stability, reduce the reflection, increase the viewing angle, and enhance the perceived brightness. It also provides resistance to dust particles and shows a better image in general.

It is the perfect choice for a wide variety of applications, including industrial automation, control panels and digital signage.



| | |
|----------------------------------|--------------------------------------|
| Product name | 21.5" Embedded Touch PC |
| Article code / EAN number | FT215V40CAPOB / 6920734022816 |

| | |
|------------------------|--|
| IP Rating | |
| IP65 Front / IP40 Back | |

| | |
|---|--------------|
| LCD Panel | |
| Screen diagonal (Inch/cm) | 21.5/54.69 |
| Display active screen size (cm) | 47.70×26.80 |
| Aspect ratio | 16:9 |
| Physical resolution | 1920×1080 |
| External Maximum showable resolution - HDMI | 1920×1080 |
| Colours displayed | 16.7M |
| Brightness (cd/m ²) | 250 |
| Contrast | 1000:1 |
| Typical reaction time Tr/ Tf (ms) | 1.5/3.5 |
| Visual Angle horizontal/vertical (°) | 170/170 |
| Backlight / Backlight Lifetime (hours) | LED / 40,000 |

| | |
|-------------------------------|--------------------------------------|
| Operation / Mechanical | |
| Operating Temperature (°C) | -10 ~ +60 |
| Humidity Range (RH) | 10% - 90% |
| Net weight (kg) | 6.80 |
| Gross weight (kg) | 8.60 (incl. cartonage) |
| Housing material | Rubber Front Case, Plastic Back Case |
| Housing (cm) L × W × H | 53.20 × 33.10 × 4.60 |
| Mounting | VESA 100 |

| | |
|----------------------------------|--|
| Included in the Delivery | |
| Power Supply (see Power section) | |
| W-LAN Antenna (RP-SMA female) | |
| Short Installation Manual | |
| Standard Stand | |

| | |
|------------------------|--|
| Expansion slots | |
| MiniPCle | |


| | |
|------------------|--|
| PC System | |
| CPU | Allwinner® V40 QuadCore |
| Chipset | Cortex A7 |
| Graphic GPU | ARM® Mali400 Mp2 Complies with OpenGL ES 2.0/1.1 |
| Audio | Integrated HI-FI 100dB Audio Codec Dual analog mic, 2x6W amplifier |
| Memory | 1GB DDR3 |
| Storage | 8GB EMMC Flash |
| Network | 10/100Mbit Network; W-LAN |
| OS | Android 6.0 |

| | |
|-----------------------|--|
| Touch Panel | |
| Touch Technology | Projected Capacitive 10-Point Multitouch |
| Touch Connector | USB |
| Touch Life (Contacts) | Unlimited |
| Surface Hardness | 7H |
| Surface Treatment | Anti-glare (chemical etching) |

| | |
|--------------------------|--|
| Power | |
| Power Indicator | Green LED |
| Power Supply | 100-240V ACDC active switching; 12V DC-Out |
| Working Power (V) | 8~18 |
| Power Consumption (W) | 23 |
| Stand-By Consumption (W) | <1 |

| | |
|-----------------------------------|--|
| Internal Connectors | |
| 1x SD-card | |
| 1x SIM-card | |
| 2x Serial | |
| 4x TTL UART | |
| 2x USB 2.0 | |
| 18/24Bit LVDS | |
| 6x GPIO | |
| 1x Line-In | |
| 1x Line-Out | |
| 1x Amplifier for 2x6W loudspeaker | |
| 1x SATA-Port | |
| 1x RTC | |
| 1x CAN Bus | |

| | |
|--|--|
| External Connectors | |
| 1x 8-18V DC-In (screwable) | |
| 1x HDMI | |
| 2x USB 2.0 | |
| 1x USB OTG | |
| 1x 10/100Mbit RJ45 Port | |
| 1x Audio-In | |
| 1x Audio-Out | |
| 1x Serial | |
| 1x GPIO RJ11 Port | |
| 1x SD-card slot | |
| 1x SIM-card slot | |
| 1x W-LAN antenna connector (RP-SMA male) | |



Corporate Headquarters

faytech AG
 Bischhäuser Aue 10
 37213 Witzenhausen
 Germany

support@faytech.com
contact@faytech.com
www.faytech.com

China: +86 755 8958 0612
 Germany: +49 5542 30374 10
 USA: +1 646 205 3214
 India: +91 11 49707436
 Japan: +070 4127 5167